

21th International Petroleum Environmental Conference
Full-Scale Implementation of In-Situ Chemical Oxidation
Persulfate Injection



Authors and Presenter

PARSONS

- Parsons' Authors:
 - Jim Leu, Ph.D., P.E.
 - Joann Lin, E.I.T.
 - Michelle Morales, E.I.T.
 - Susan Ferris, P.G.

Parsons' Presenter:
Jim Leu, Ph.D., P.E.
Jim.Leu@parsons.com


Presentation Overview

- Site Background
- Bench Test
- Groundwater Modeling
 - Capture Zone Analysis (MODFLOW)
 - By-products Impacts Evaluation (MT3D)
- Full Scale Implementation
 - Induced Resonance Well Rehabilitation
 - Injection and Monitoring Program
 - Geotechnical Monitoring
 - GWETS

Site Background - Site Specific Information

- Former natural gas processing station (1960 - 1980s)
- Interbedded layers of sand and silty sand (0 - 30 ft bgs)
- Three hydrostratigraphic layers:
 - **Shallow unconfined zone (15 - 30 ft bgs)**
 - Confining layer (30 – 70 ft bgs)
 - Deep zone (70 – 90 ft bgs)
- Shallow unconfined zone
 - Groundwater velocity: 0.4 ft/day
 - Flow direction: southeast and northeast

Site Background - Cross Section



Site Background – Nature and Extent of Impacts

- Chemicals of Concern identified in **saturated zone**:
 - Gasoline Range Organics (GRO)
 - Diesel Range Organics (DRO)
 - Motor Oil Range Organics (ORO)

Matrix	GRO	DRO	ORO
Groundwater ($\mu\text{g/L}$)	3,500	3,700	440
Clean-up Levels ($\mu\text{g/L}$)	100	100	100

Bench Test

- Oxidants
 - Persulfate
 - Stabilized Peroxide
 - Persulfate and Stabilized Peroxide




Bench Test – Results/Conclusions

- COC Removal
 - Three oxidants reduced DRO in groundwater
- Byproduct Effects
 - Persulfate – TDS, sulfate, and pH
 - Stabilized peroxide – acetone
- Soil Buffering
 - Mild buffering capacity
 - More remaining alkalinity from persulfate
- Longevity Test – Stabilized Peroxide
 - Insignificant temperature change
 - Off-gas generated


Bench Scale Test - Recommendations

- **Persulfate Selected:**
 - Equivalent COC removal in GW
 - Byproduct effects (no acetone)
 - Persistent
- **Persulfate Dose:**
 - 33 g/L from SOD & theoretical COCs requirements
 - Higher than dosages used in COC removal

MODFLOW - Capture Zone




Existing 5 EWs at 3 gpm




Proposed EWs at 3 gpm

MT3D - TDS Impact Distribution




ONE MONTH AFTER



NINE MONTHS AFTER

MT3D - TDS Concentration at EW-5



Groundwater Modeling – Summary and Conclusion

- Existing EWs capture byproduct impacts
- Proposed EW-5 and EW-7 @ 3 gpm will capture byproduct impacts
- TDS at EW-5
 - Maximum concentration in 4 months
 - Back to baseline concentration in 12 months
- GWETS will be initiated in 3 months

Full Scale Persulfate Injection



Induced Resonance Well Rehabilitation

- Nitrogen gas pulsing
 - Pressure : 300 psi
 - Pulse rate : 1 - 2 seconds
- Groundwater pumping
 - Turbidity: < 50 NTU
- Cycle: 2 – 4
- Specific capacity increase
 - EW-5 : 150%
 - EW-7 : 150%



Persulfate Injection and Monitoring Summary


■ Persulfate Injection

- Solution: 10% sodium persulfate
- Volume: 1,400 gal/well
- Points: 12
- Pressure: 5 - 65 psi
- Rate: 0.5 - 5 gpm
- Duration: 1.5 weeks


■ Groundwater Monitoring

- Performance well: 4 (COCs)
- Compliance well: 8 (COCs, Byproducts)
- Transition well: 2 (COCs, Byproducts)

Persulfate Injection Plan (DRO Concentration Contour)



Groundwater Monitoring Well Locations JLin5




Slide 18

JLin5

Need to remove the street names.

Joann Lin, 9/25/2014

Persulfate Injection P&ID



Persulfate Injection Equipment



REAGENT MIXING TANK



INJECTION MANIFOLD



INJECTION TOOL

Vertical Drilling and Injection



Drilling/Injection Specifics

- Open Field
- Points: 6
- Depth: 15 - 23 ft vertical

Angle Drilling and Injection



Drilling/Injection Specifics


- Below the Building
- Points: 6
- Angles: 10 - 20 degrees
- Depth: 14 - 21 ft vertical

Geotechnical Monitoring Results


- Visual inspection: No observable changes
- Crack monitoring:
 - No new cracks induced
- Settlement monitoring:
 - Differential settlement less than 1%
 - Total settlement less than 0.5 inches



GRO Concentration Trends in Treatment Zone Wells




GRO Concentration Contour




BEFORE


AFTER



DRO Concentration Trends in Treatment Zone Wells




DRO Concentration Contour



BEFORE

AFTER




Persulfate Injection Contingency Plan

- Trigger: TDS concentrations at transition wells (TW-2, TW-3) exceed 20% of baseline concentration
- Response: Initiate GWETS at extraction wells


MODFLOW - Capture Zone for TDS Impacts

JLin8



**3 Months Later
2 EWs at 2 gpm**

**9 Months Later
3 EWs at 5.5 gpm**




Slide 29

JLin8

It's hard to see the Site and hard to identify the extraction wells and transition wells.

Joann Lin, 9/25/2014

TDS Concentration Trends in Downgradient Groundwater Wells



Persulfate Injection Results

- GWETS initiated to capture TDS and sulfate after 3 months
- GRO decreased without rebound, DRO decreased but rebounded
- Metals increased insignificantly
- Monitoring Parameters
 - ORP - increased
 - Conductivity – increased
 - Sulfate – increased
 - pH - decreased
 - Temperature – no change



Persulfate Injection Conclusions

- Successfully destroys COCs in saturated zone
- Byproduct impacts
 - Injected chemicals captured
 - Oxidized chemicals contained
- Sustained persulfate concentration
- Induced resonance increased well yield
- Angle injection caused minimal geotechnical impacts
- Hydrogen sulfide not generated

Acknowledgements

- Special thanks to OTG EnviroEngineering Solutions, PRIMA and VIRONEX for their outstanding implementation